

Digital probes for measuring conductivity FYD 741 LFE01 and FYD 741 LFP with ALMEMO® D7 plug



ALMEMO® 202

Just one single probe for measuring conductivity from very low (10 µS/cm) up to very high levels (500 mS/cm)

4-contact graphite electrode with high linearity across the whole measuring range

Integrated NTC sensor for temperature compensation of measured conductivity values

Suitable for the latest ALMEMO® V7 devices, including professional measuring instrument ALMEMO® 202 and precision measuring instrument ALMEMO® 710.

05/2015 • We reserve the right to make technical changes.

Technical data and functions

The digital conductivity probe provides this high level of precision irrespective of any extension cables used and of any processing in the ALMEMO® V7 display device / data logger. Overall accuracy is determined exclusively by the conductivity electrode and the ALMEMO® D7 plug.

All parameters for the sensor can be programmed end-to-end via the programming menu on the ALMEMO® V7 measuring instrument. The desired measuring range can be selected and

temperature compensation can be activated or deactivated.

The temperature coefficient of the solution to be measured, if known, can also be programmed.

The probe is delivered already adjusted and ready-to-use. The electrode's measured cell constant can also be entered, if so required, and / or the probe can be adjusted using a reference solution.

Common technical data FYD 741 LFE01 and FYD 741 LFP ALMEMO® D7 plug with A/D converter

Measuring method	Electrical conductivity measurement with AC voltage (approx. 1 kHz)	Temperature coefficient	Natural surface water or linear in range 0.00 to 9,99
Measuring ranges		Linearization NTC	Calculated error-free (not an approximation)
Range DLF1	up to maximum 500.00 µS/cm	Nominal temperature	+23 °C ±2 K
	Resolution 0.01 µS/cm	Temperature drift	0.004 % / K (40 ppm)
Range DLF2	up to 50.000 mS/cm	Refresh time	2.5 seconds
	Resolution 0.001 mS/cm (factory default settings)	Sleep mode on the device	possible with wakeup delay of 5 seconds
Range DLF3	with FYD 741 LFE01 up to 500.00 mS/cm	Supply voltage	6 to 13 VDC, from ALMEMO® device (sensor supply voltage)
	with FYD 741 LFP up to 200.00 mS/cm	Current consumption	approx. 10 mA
	Resolution 0.01 mS/cm		
Range NTC	Resolution 0.01 K		
Temperature compensation	either automatic or non-compensated		

Accessories

	Order no.
Reference solution for monitoring / calibration	
Conductivity 147 µS/cm, Container 250 ml	ZB96LFRL2
Conductivity 2.77 mS/cm, Container 250 ml	ZB96LFRL
Conductivity 12.88 mS/cm, Container 250 ml	ZB96LFRL4
Conductivity 111.8 mS/cm, Container 250 ml	ZB96LFRL3

Digital probe for measuring conductivity FYD 741 LFP



Probe for process applications

General description and common technical data
see previous page

Technical data FYD 741 LFP

Uses	Process applications
Conductivity	10 µS/cm up to 200 mS/cm
Temperature	0 to +70 °C
Pressure	up to 16 bar under nominal conditions
Process connection	Thread G ¾-inch Fitted length 145 mm
Electrode type	4-contact graphite electrode electrically connected to the power supply (ALMEMO® device ground)
Cell constant	approx. 0.5 cm ⁻¹
Temperature sensor	NTC 10 kilohms, integrated
Accuracy	
Conductivity	±3% of meas. value ±0.2% of final value under nominal conditions
Temperature	±0.2 K under nominal conditions
Nominal conditions	+25 °C ±2 K
Minimum immersion depth	30 mm
Electrode shaft	Material PVC-C diameter 20 mm, length 130 mm
Connecting cable	length = 1.5 meters, permanently fitted, with ALMEMO® D7 plug

Digital probe for measuring conductivity FYD 741 LFE01



Probe for laboratory applications

General description and common technical data
see previous page

Technical data FYD 741 LFE01

Uses	Laboratory applications
Conductivity	10 µS/cm up to 200 mS/cm, on demand up to 500 mS/cm
Temperature	0 to +80 °C
Pressure	Ambient pressure (unpressurized)
Electrode type	4-contact graphite electrode electrically connected to the power supply (ALMEMO® device ground)
Cell constant	approx. 0.5 cm ⁻¹
Temperature sensor	NTC 30 kilohms, integrated
Accuracy	
Conductivity	±2% of meas. value ±0.2% of final value under nominal conditions
Temperature	±0.2 K under nominal conditions
Nominal conditions	+25 °C ±2 K
Minimum immersion depth	30 mm
Electrode shaft	Material PC (+ABS) diameter 12 mm, length 120 mm
Connecting cable	length = 1 meter, permanently fitted, with ALMEMO® D7 plug

Variants

Digital probe for measuring conductivity, integrated temperature sensor, with process connection G ¾-inch, permanently fitted cable with ALMEMO® D7 plug,
probe for process applications

Order no.

FYD741LFP

Variants

Digital probe for measuring conductivity, integrated temperature sensor, with permanently fitted cable with ALMEMO® D7 plug,
probe for laboratory applications

Order no.

FYD741LFE01